

# SPECIFICATIONS



## SPECIFICATION SHEET 3<sup>rd</sup> Generation TriPac<sup>®</sup> Auxiliary Power Unit



### MODELS AND OPTIONS

#### TriPac Standard Model

#### TriPac with Aftertreatment Device Model

#### Cold Weather Starting

Arctic Package

#### Solar

- Solar Kit, APU 40W White
- Solar Kit, APU 110W White
- Solar Kit, APU 110W Black

#### Air Flow Distribution

Tower Kit

#### Truck Integration

- Truck Integration Harness \*
- Truck Integration Harness w/ Switch \*
- Truck Integration Harness w/ Switch (w/ATD) \*\*

#### Hour Meters

- Dual Hour Meters (Engine Hours & Heater Hours)
- Single Hour Meter (Engine Hours)

#### Cab Air Damper

Backflow Preventer Kit

#### Inverter

Inverter - 2000 Watt Pure Sine Wave

#### Heater

- Heater AX2 (D2) Delete
- High Output Heater Upgrade AX2 (D4)

#### Exhaust

- Stainless Steel Exhaust Extension \*
- Stainless Steel Exhaust Extension for ATD\*\*

#### Appearance

- Stainless Steel Condenser
- Appearance Package (Diamond Plate Top Cover)

#### Mounting

Direct Mount Kit 1.5" Spacer

#### Engine

- Gates<sup>®</sup> PowerGrip<sup>®</sup> Hose Clamp
- Closed Loop Cooling

#### Telematics

- Hardware + 4YRS service
- Hardware + 3YRS service

#### Delete Options

- Fuel Pickup Tube Delete Option
- Precooler Fan Cover Delete Option

\* Specific to Standard Model \*\* Specific to Aftertreatment Device Model

